

Picture may differ from original product




SX Rubber Series

Wheel Diameter × Wheel Width 125 x 40mm

YJ-12040305151300 Copy model no.

Wheel Diameter(D)	Load Capacity (Dynamic)	Wheel Bearing
125mm	**200kgs**	**Without Bearing**

- Made of Resilient Rubber
- **Features excellent handling comfort, good Floor Surface Preservation, and Shock-Absorbing.**
- **Excellent resistance to chemicals, solvents, and corrosion.**
- **Suitable for industrial and heavy-duty wheels.**
- **Rubber, Black, Curved Surface, V-pattern**
- **Increases grip and effectively improves slip resistance.**
- Wheel Center: cast iron core
- Outer packaging: rubber
- Bearings: —

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet

Product Data Sheet

Metric | Imperial

Wheel Diameter(D)	**125mm**	Wheel Width(T2)	**39.5mm**
Wheel Bearing	**Without Bearing**	Axle Bore(d)	**—**
Axle Bore(S)	**35mm**	Bearing Bore Depth(t)	**11mm**
Hub Lenth(T1)	**40mm**	Hardness Of Tread	**85±5° Shore A**
Load Capacity (Dynamic)	**200kgs**	Load Capacity (Static)	**300kgs**
Temperature	**-20°C to +120°C**	Electrical Conductivity	**N/A**
Anti-Static	**N/A**	Weight	**0.76kgs**
Standard	**ISO22883**		

* For any deviation between metric and imperial spec, please refer to the metric spec.

Performance

Rolling Smoothness
Max. 5 points Score: 3

Quiet Operation
Max. 5 points Score: 4

Floor Surface Preservation
Max. 5 points Score: 4

Downloads

PDF **1203-EN-YJ2026110401.pdf**
Product Data Sheet

© 2026 DERSHENG CO., LTD. All rights reserved.