
Product Data Sheet

# 1112-1 2" Wide General Purposes Caster Series

W Resolute (Pearlescent Light Gray) Wheel Diameter × Wheel Width 100×50mm

A

KS-11120601452011



Picture may differ from original product

Modible Casters, Welded Caster Fork, black paint finish
Base plate Mounting Type, 85x70mm Bolt Hole Spacing
Reinforced Polypropylene rubber elastomer (TPR)
Cast Iron pearlescent light gray, Bearing—Ball Bearings

Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel Center: High-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product

## Technical Data


◉ Metric ○ Imperial

| | |
|---|---|
| Wheel Diameter | 100mm |
| Wheel Width | 50mm |
| Wheel Bearing | Wheels With Ball Bearings |
| Plate Size | 115 x 100mm |
| Bolt Hole Spacing | 85 x 70mm |
| Plate Hole | 20 x 11mm |
| Offset | 25mm |
| Swivel Interference | 158mm |
| Overall Height | 141.6mm |
| Swivel Radius | 79mm |
| Hardness Of Tread | 72±5° Shore A |
| Load Capacity (Dynamic) | 270kgs |
| Load Capacity (Static) | 405kgs |
| Temperature | -20°C to +60°C |
| Fork Type | Swivel Caster |
| Stainless | N/A |
| Electrical Conductivity | N/A |
| Anti-Static | N/A |
| Weight | 1.88kgs |
| Standard | ISO22883 |


## Advantages at a glance

| | |
|---|---|
| Rolling Resistance | ● ● ● ● ● |
| Operating Noise | ● ● ● ● ● |
| Floor Surface Preservation | ● ● ● ● ● |

## Dimensions




## Mounting




* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2026 DershengInternational www.dersheng.com