
Product Data Sheet

1139 Medium Duty General Purposes Caster Series

PU (Black flat) Wheel Diameter x Wheel Width 75 × 32mm

EAN

YJ-11390300335023



Picture may differ from original product

Swivel Caster, thread-Riveted Stamping Fork—M12-P1.75 Extended control lever surface, Mounting Type - Threaded Stem device Cast Iron Wheel Center, High Quality Polyurethane Wheel Tread Black, Bearing—Ball Bearing.

Wheel tread: Made of high quality polyurethane

Wheel Center: cast iron core

Drawings are for reference only and may differ from the product

Technical Data


◉ Imperial ○ Metric

Wheel Diameter	3 "
Wheel Width	1-5/16 "
Wheel Bearing	Wheels With Ball Bearings
Threaded Stem	M12-P1.75
Threaded Size	5/8 "
Offset	1-1/2 "
Swivel Interference	6-3/16 "
Overall Height	4-3/16 "
Swivel Radius	3-1/8 "
Hardness Of Tread	93±5° Shore A
Load Capacity (Dynamic)	198lbs
Load Capacity (Static)	298lbs
Temperature	-4°F to +158°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	2.1lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 DershengInternational www.dersheng.com